









## Écrous à sertir en aveugle AFM-G


aluminium 🗐

tête plate | cylindrique lisse | borgne









EN AW-5754 [AIMg3]

M	<b>‡</b>	1	N°		
M4	0,3 - 2,0	15,5	10854040200		500
<b>D</b> 6,0	<b>k</b> 0,8	<b>d</b> <sub>k</sub> 10,0	I <sub>1</sub> max. 13,5	→ 3 Nm	‡ 2600 N
M5	0,3 - 3,0	18,5	10854050300		500
<b>D</b> 7,0	<b>k</b> 1,0	<b>d</b> <sub>k</sub> 11,0	<b>I₁ max.</b> 15,5	√ 4 Nm	\$ 4300 N
M6	0,5 - 3,0	22,0	2,0 10854060300		500
IVIO	3,0 - 4,5	23,0	10854060450		500
<b>D</b> 9,0	<b>k</b> 1,5	<b>d</b> <sub>k</sub> 13,0	<b>I₁ max.</b> 18,5	→ 6 Nm	<b>‡</b> 6700 N

М	<b>*</b>	1	N°		
M8	0,5 - 3,0	26,5	10854080300		250
<b>D</b> 11,0	<b>k</b> 1,5	<b>d</b> <sub>k</sub> 16,0	I <sub>1</sub> max. 23,0		‡ 11000 N
M10	1,0 - 3,0	32,5	10854100300		250
<b>D</b> 13,0	<b>k</b> 2,0	<b>d</b> <sub>k</sub> 19,0	<b>I₁ max.</b> 28,5	<b>○ 28 Nm</b>	‡ 17500 N