

Écrous à sertir en aveugle AFM




 aluminium

tête plate | cylindrique lisse | ouvert



DONNÉES
CAO
EN LIGNE

Série
850



EN AW-5754 [AlMg3]

M		l	N°	
M3	0,3 - 2,0	8,5	10850030200	500
D 5,0	k 0,8	dk 7,0	l₁ max. 6,0	 1 Nm  1500 N
M4	0,5 - 3,0	11,0	10850040300	500
	2,5 - 4,0	12,0	10850040400	500
D 6,0	k 0,8	dk 10,0	l₁ max. 8,0	 3 Nm  2600 N
M5	0,5 - 3,0	12,0	10850050300	500
	2,5 - 4,5	13,5	10850050450	500
	4,0 - 6,0	15,0	10850050600	500
D 7,0	k 1,0	dk 11,0	l₁ max. 9,0	 4 Nm  4300 N
M6	0,5 - 3,0	14,5	10850060300	500
	3,0 - 4,5	16,0	10850060450	500
D 9,0	k 1,5	dk 13,0	l₁ max. 11,0	 6 Nm  6700 N

M		l	N°	
M8	0,5 - 3,0	17,0	10850080300	500
	3,0 - 5,5	19,5	10850080550	500
	5,5 - 7,5	21,5	10850080750	500
D 11,0	k 1,5	dk 16,0	l₁ max. 13,5	 18 Nm  11000 N
M10	1,0 - 4,0	22,0	10850100400	250
	3,0 - 6,0	24,0	10850100600	250
D 13,0	k 2,0	dk 19,0	l₁ max. 16,5	 28 Nm  17500 N
M12	1,0 - 4,0	24,0	10850120400	100
D 16,0	k 2,0	dk 23,0	l₁ max. 18,5	 45 Nm  28000 N