

Écrous à sertir en aveugle ASM

aluminium




tête fraisée | cylindrique lisse | ouvert



FILM

DONNÉES
CAO
EN LIGNE

Série
851



EN AW-5754 [AlMg3]

M		l	N°	
M4	1,5 - 3,5	11,5	10851040350	500
D 6,0	k 1,5	dk 8,3	l1 max. 8,0	3 Nm
M5	2,0 - 4,0	13,0	10851050400	500
D 7,0	k 1,5	dk 9,3	l1 max. 9,0	4 Nm
M6	1,5 - 4,5	16,0	10851060450	500
	4,0 - 6,0	17,5	10851060600	500
D 9,0	k 1,5	dk 11,3	l1 max. 11,0	6 Nm

M		l	N°	
M8	1,5 - 4,5	18,5	10851080450	500
	4,0 - 6,0	20,0	10851080600	500
D 11,0	k 1,5	dk 13,3	l1 max. 13,5	18 Nm
M10	1,5 - 3,0	20,5	10851100300	250
	3,0 - 4,5	22,0	10851100450	250
	3,5 - 6,5	24,0	10851100650	250
D 13,0	k 1,5	dk 15,5	l1 max. 16,5	28 Nm
M12	1,7 - 4,5	26,0	10851120450	100
D 16,0	k 1,9	dk 19,0	l1 max. 17,5	45 Nm