

Écrous à sertir en aveugle EFM-R




inox A2

tête plate | cylindrique cranté | ouvert



DONNÉES
CAO
EN LIGNE

Série
848



[1.4567]

M		l	N°	
M3	0,5 - 2,0	10,0	10848030200	500
D 5,0	k 0,8	dk 8,0	l ₁ max. 7,0	↕ 4000 N
M4	0,5 - 2,5	11,0	10848040250	500
	2,5 - 4,0	12,5	10848040400	500
D 6,0	k 0,8	dk 9,0	l ₁ max. 8,0	↕ 6500 N
M5	0,5 - 3,0	12,0	10848050300	500
	3,0 - 4,5	13,5	10848050450	500
D 7,0	k 1,0	dk 10,0	l ₁ max. 8,5	↕ 10000 N

M		l	N°	
M6	0,5 - 3,0	14,5	10848060300	500
	3,0 - 5,0	16,0	10848060500	500
D 9,0	k 1,5	dk 12,0	l ₁ max. 10,0	↕ 17000 N
M8	0,5 - 3,0	16,0	10848080300	500
	3,0 - 5,5	18,5	10848080550	250
D 11,0	k 1,5	dk 15,0	l ₁ max. 12,0	↕ 25000 N
M10	1,0 - 3,5	19,0	10848100350	250
	3,5 - 6,0	21,5	10848100600	250
D 13,0	k 2,0	dk 17,0	l ₁ max. 14,0	↕ 38000 N