











## Écrous à sertir en aveugle HEXAFORM-KLSK-G

acier zingué 🗐

tête affleurante | hexagonal | borgne










C4C [1.0303]

M	<b>‡</b>	1	N <sub>o</sub>		
M4	0,5 - 2,5	16,0	10887040250		500
<b>SW</b> 6,0	<b>SW</b> <sup>2</sup> 6,6	<b>k</b> 0,5	I <sub>1</sub> max. 10,0		\$ 5200 N
M5	0,5 - 3,0	20,0	10887050300		500
<b>SW</b> 7,0	SW <sup>2</sup> 7,7	<b>k</b> 0,6	I <sub>1</sub> max. 12,5	→ 7 Nm	\$ 9500 N
M6	0,8 - 3,0	22,0	10887060300		500
<b>SW</b> 9,0	<b>SW</b> <sup>2</sup> 9,8	<b>k</b> 0,7	<b>I₁ max.</b> 16,0		\$ 16500 N







M	<b>*</b>	1	N°		
M8	0,5 - 3,5	25,5	25,5 10887080350		250
IVIO	3,0 - 6,0	28,0	10887080600		250
<b>SW</b> 11,0	<b>SW<sup>2</sup></b> 11,8	<b>k</b> 0,7	<b>I₁ max.</b> 17,5		\$ 23500 N
M10	1,0 - 3,5	28,0	10887100350		250
<b>SW</b> 13,0	<b>SW<sup>2</sup></b> 14,3	<b>k</b> 0,9	I <sub>1</sub> max. 20,0	→ 55 Nm	<b>‡</b> 37000 N