

Écrous à sertir en aveugle HEXAFORM-KLSK





acier zingué

tête affleurante | hexagonal | ouvert



DONNÉES
CAO
EN LIGNE

Série
892



C4C [1.0303]

M		I	N°	
M4	0,6 - 2,0	11,0	10892040200	500
	2,0 - 4,0	13,0	10892040400	500
SW 6,0	SW² 6,6	k 0,6	I₁ max. 7,5	5 Nm 5000 N
M5	0,7 - 3,0	13,5	10892050300	500
	3,0 - 5,5	16,0	10892050550	500
SW 7,0	SW² 7,7	k 0,7	I₁ max. 8,5	7 Nm 9000 N
M6	0,8 - 3,0	15,5	10892060300	500
	3,0 - 5,5	18,0	10892060550	500
SW 9,0	SW² 9,8	k 0,8	I₁ max. 10,5	13 Nm 16000 N

M		I	N°	
M8	0,8 - 3,0	18,5	10892080300	250
	3,0 - 6,0	21,5	10892080600	250
SW 11,0	SW² 11,8	k 0,8	I₁ max. 13,0	25 Nm 23000 N
M10	1,0 - 3,5	22,5	10892100350	250
	3,0 - 6,0	23,5	10892100600	250
SW 13,0	SW² 14,3	k 0,9	I₁ max. 16,5	55 Nm 36500 N
M12	1,0 - 4,0	24,5	10892120400	100
SW 16,0	SW² 17,3	k 0,9	I₁ max. 17,5	85 Nm 55000 N