

# Écrous à sertir en aveugle HEXATOP-E-KLSK-G





inox A2

tête affleurante | semi-hexagonal | borgne



DONNÉES  
**CAO**  
EN LIGNE

Série  
**805**



[1.4567]

| M             |                           | l            | N°                             |              |
|---------------|---------------------------|--------------|--------------------------------|--------------|
| <b>M4</b>     | 0,5 - 2,5                 | 16,0         | 10805040250                    | 500          |
| <b>SW 6,0</b> | <b>SW<sup>2</sup> 6,8</b> | <b>k 0,5</b> | <b>l<sub>1</sub> max. 10,5</b> | 5 Nm  6000 N |
| <b>M5</b>     | 0,5 - 3,0                 | 18,0         | 10805050300                    | 500          |
| <b>SW 7,0</b> | <b>SW<sup>2</sup> 7,8</b> | <b>k 0,5</b> | <b>l<sub>1</sub> max. 12,5</b> | 7 Nm  9500 N |

| M              |                            | l            | N°                             |                |
|----------------|----------------------------|--------------|--------------------------------|----------------|
| <b>M6</b>      | 0,5 - 3,0                  | 21,0         | 10805060300                    | 500            |
| <b>SW 9,0</b>  | <b>SW<sup>2</sup> 9,8</b>  | <b>k 0,7</b> | <b>l<sub>1</sub> max. 16,0</b> | 13 Nm  16000 N |
| <b>M8</b>      | 0,5 - 3,0                  | 23,5         | 10805080300                    | 250            |
| <b>SW 11,0</b> | <b>SW<sup>2</sup> 11,8</b> | <b>k 0,7</b> | <b>l<sub>1</sub> max. 17,5</b> | 25 Nm  26000 N |