

# Écrous à sertir en aveugle SFM-G




acier zingué

tête plate | cylindrique lisse | borgne



DONNÉES  
**CAO**  
EN LIGNE

Série  
**856**



C4C [1.0303]

| M         |           | l       | N°                       |           |
|-----------|-----------|---------|--------------------------|-----------|
| <b>M5</b> | 0,5 - 3,0 | 17,0    | 10856050300              | 500       |
| D 7,0     | k 1,0     | dk 11,0 | l <sub>1</sub> max. 15,5 | ↻ 6 Nm    |
|           |           |         |                          | ↕ 9500 N  |
| <b>M6</b> | 0,5 - 3,0 | 21,5    | 10856060300              | 500       |
| D 9,0     | k 1,2     | dk 12,0 | l <sub>1</sub> max. 16,0 | ↻ 11 Nm   |
|           |           |         |                          | ↕ 16500 N |

| M         |           | l       | N°                       |           |
|-----------|-----------|---------|--------------------------|-----------|
| <b>M8</b> | 0,5 - 3,5 | 25,2    | 10856080350              | 250       |
| D 11,0    | k 1,3     | dk 14,0 | l <sub>1</sub> max. 17,5 | ↻ 24 Nm   |
|           |           |         |                          | ↕ 23500 N |