

Écrous à sertir en aveugle SSM

acier zingué




tête fraisée | cylindrique lisse | ouvert



FILM

DONNÉES
CAO
EN LIGNE

Série
853



C4C [1.0303]

M		l	N°		
M4	1,5 - 3,5	11,5	10853040350	500	
D 6,0	k 1,5	d _k 8,3	l ₁ max. 8,0	 4 Nm	 5200 N
M5	1,5 - 4,0	13,0	10853050400	500	
D 7,0	k 1,5	d _k 9,3	l ₁ max. 9,0	 6 Nm	 9500 N
M6	1,5 - 4,5	16,0	10853060450	500	
	4,5 - 6,0	17,5	10853060600	500	
D 9,0	k 1,5	d _k 11,3	l ₁ max. 11,0	 11 Nm	 16500 N

M		l	N°		
M8	1,5 - 4,5	18,5	10853080450	250	
	4,5 - 6,0	20,0	10853080600	250	
D 11,0	k 1,5	d _k 13,3	l ₁ max. 13,5	 24 Nm	↑ 23500 N
M10	3,0 - 4,5	22,0	10853100450		250
	4,5 - 6,0	23,5	10853100600		250
	6,0 - 9,0	26,5	10853100900		250
D 13,0	k 1,5	d _k 15,2	l ₁ max. 16,5	 50 Nm	↑ 37000 N