







## Écrous à sertir en aveugle UNIVERSAL-R


acier zingué 🗐

tête affleurante | cylindrique cranté | ouvert









C4C [1.0303]

| M            | #            | - 1       | Nº                       |           |     |
|--------------|--------------|-----------|--------------------------|-----------|-----|
| M4           | 0,5 - 3,0    | 10,5      | 10871400000              |           | 500 |
| <b>D</b> 7,0 | <b>k</b> 0,4 | $d_k$ 8,0 | <b>I₁ max.</b> 7,0       | \$ 6000 N |     |
| M5           | 0,5 - 3,0    | 11,5      | 10871500000              |           | 500 |
| <b>D</b> 7,0 | <b>k</b> 0,4 | $d_k$ 8,0 | I <sub>1</sub> max. 8,0  | \$ 7500 N |     |
| M6           | 0,5 - 3,0    | 13,0      | 10871600000              |           | 500 |
| <b>D</b> 8,0 | <b>k</b> 0,4 | $d_k 9,0$ | I <sub>1</sub> max. 10,0 | ‡ 10000 N |     |

| М             | *            | I                          | Nº                  |           |     |
|---------------|--------------|----------------------------|---------------------|-----------|-----|
| M8            | 0,5 - 3,0    | 15,5                       | 10871800000         |           | 500 |
| <b>D</b> 10,0 | <b>k</b> 0,4 | <b>d</b> <sub>k</sub> 11,5 | <b>I₁ max.</b> 11,5 | ‡ 14000 N |     |
| M10           | 0,5 - 3,0    | 17,5                       | 10871100000         |           | 250 |
| <b>D</b> 12,0 | <b>k</b> 0,4 | <b>d</b> <sub>k</sub> 13,0 | <b>I₁ max.</b> 13,0 | ‡ 17500 N |     |