

Écrous à sertir en aveugle AFM

 aluminium




tête plate | cylindrique lisse | ouvert



FILM

DONNÉES
CAO
EN LIGNE

Série
850



EN AW-5754 [AlMg3]

M		I	N°		
M3	0,3 - 2,0	8,5	10850030200	500	
D 5,0	k 0,8	d _k 7,0	l ₁ max. 6,0	 1 Nm	 1500 N
M4	1,5 - 3,0	11,0	10850040300	500	
	2,5 - 4,0	12,0	10850040400	500	
D 6,0	k 0,8	d _k 10,0	l ₁ max. 8,0	 3 Nm	 2600 N
M5	0,5 - 3,0	12,0	10850050300	500	
	2,5 - 4,5	13,5	10850050450	500	
	4,0 - 6,0	15,0	10850050600	500	
D 7,0	k 1,0	d _k 11,0	l ₁ max. 9,0	 4 Nm	 4300 N
M6	0,5 - 3,0	14,5	10850060300	500	
	3,0 - 4,5	16,0	10850060450	500	
D 9,0	k 1,5	d _k 13,0	l ₁ max. 11,0	 6 Nm	 6700 N

M		I	N°		
M8	0,5 - 3,0	17,0	10850080300	500	
	3,0 - 5,5	19,5	10850080550	500	
	5,5 - 7,5	21,5	10850080750	500	
D 11,0	k 1,5	d _k 16,0	l ₁ max. 13,5	 18 Nm	 11000 N
M10	1,0 - 4,0	22,0	10850100400		250
	3,0 - 6,0	24,0	10850100600		250
D 13,0	k 2,0	d _k 19,0	l ₁ max. 16,5	 28 Nm	 17500 N
M12	1,0 - 4,0	24,0	10850120400		100
D 16,0	k 2,0	d _k 23,0	l ₁ max. 18,5	 45 Nm	 28000 N