

# Écrous à sertir en aveugle ASM

 aluminium




tête fraisée | cylindrique lisse | ouvert



FILM

DONNÉES  
CAO  
EN LIGNE

Série  
851



EN AW-5754 [AlMg3]

| M         |  | I       | N°                       |  |
|-----------|-----------------------------------------------------------------------------------|---------|--------------------------|-----------------------------------------------------------------------------------|
| <b>M4</b> | 1,5 - 3,5                                                                         | 11,5    | 10851040350              | 500                                                                               |
| D 6,0     | k 1,5                                                                             | dk 8,3  | l <sub>1</sub> max. 8,0  | ↻ 3 Nm                                                                            |
| <b>M5</b> | 2,0 - 4,0                                                                         | 13,0    | 10851050400              | 500                                                                               |
| D 7,0     | k 1,5                                                                             | dk 9,3  | l <sub>1</sub> max. 9,0  | ↻ 4 Nm                                                                            |
| <b>M6</b> | 1,5 - 4,5                                                                         | 16,0    | 10851060450              | 500                                                                               |
|           | 4,0 - 6,0                                                                         | 17,5    | 10851060600              | 500                                                                               |
| D 9,0     | k 1,5                                                                             | dk 11,3 | l <sub>1</sub> max. 11,0 | ↻ 6 Nm                                                                            |

| M          |  | I       | N°                       |  |
|------------|-----------------------------------------------------------------------------------|---------|--------------------------|-------------------------------------------------------------------------------------|
| <b>M8</b>  | 1,5 - 4,5                                                                         | 18,5    | 10851080450              | 500                                                                                 |
|            | 4,0 - 6,0                                                                         | 20,0    | 10851080600              | 500                                                                                 |
| D 11,0     | k 1,5                                                                             | dk 13,3 | l <sub>1</sub> max. 13,5 | ↻ 18 Nm                                                                             |
| <b>M10</b> | 1,5 - 3,0                                                                         | 20,5    | 10851100300              | 250                                                                                 |
|            | 3,0 - 4,5                                                                         | 22,0    | 10851100450              | 250                                                                                 |
|            | 3,5 - 6,5                                                                         | 24,0    | 10851100650              | 250                                                                                 |
| D 13,0     | k 1,5                                                                             | dk 15,5 | l <sub>1</sub> max. 16,5 | ↻ 28 Nm                                                                             |
| <b>M12</b> | 1,7 - 4,5                                                                         | 26,0    | 10851120450              | 100                                                                                 |
| D 16,0     | k 1,9                                                                             | dk 19,0 | l <sub>1</sub> max. 17,5 | ↻ 45 Nm                                                                             |