

# Écrous à sertir en aveugle ESM




inox A2

tête fraisée | cylindrique lisse | ouvert



DONNÉS  
CAO  
EN LIGNE

Série  
**859**



[1.4567]

| M         |           | l       | Nr.                      |                      |
|-----------|-----------|---------|--------------------------|----------------------|
| <b>M5</b> | 1,5 - 4,5 | 13,5    | 10859050450              | 500                  |
| D 7,0     | k 1,5     | dk 10,0 | l <sub>1</sub> max. 8,5  | ↻ 6 Nm    ⬆ 11000 N  |
| <b>M6</b> | 1,5 - 4,5 | 16,0    | 10859060450              | 500                  |
| D 9,0     | k 1,5     | dk 12,0 | l <sub>1</sub> max. 10,0 | ↻ 11 Nm    ⬆ 16000 N |

| M         |           | l       | Nr.                      |                      |
|-----------|-----------|---------|--------------------------|----------------------|
| <b>M8</b> | 1,5 - 4,5 | 18,0    | 10859080450              | 500                  |
|           | 4,5 - 6,5 | 20,0    | 10859080650              | 250                  |
| D 11,0    | k 1,5     | dk 14,0 | l <sub>1</sub> max. 11,5 | ↻ 24 Nm    ⬆ 27000 N |