




# Écrous à sertir en aveugle HEXAFORM-FK

acier zingué

tête plate | hexagonal | ouvert



C4C [1.0303]

| M         |           | I       | N°           |                      |
|-----------|-----------|---------|--------------|----------------------|
| <b>M4</b> | 0,5 - 2,0 | 10,0    | 10868040200  | 500                  |
| SW 6,0    | k 1,0     | dk 9,0  | li max. 7,5  | ↺ 5 Nm<br>↕ 5200 N   |
| <b>M5</b> | 0,5 - 3,0 | 13,0    | 10868050300  | 500                  |
| SW 7,0    | k 1,0     | dk 10,0 | li max. 8,5  | ↺ 7 Nm<br>↕ 9500 N   |
| <b>M6</b> | 0,5 - 3,0 | 14,5    | 10868060300  | 500                  |
|           | 3,0 - 5,0 | 16,5    | 10868060500  | 500                  |
| SW 9,0    | k 1,5     | dk 13,0 | li max. 10,5 | ↺ 13 Nm<br>↕ 16500 N |

| M          |           | I       | N°           |                      |
|------------|-----------|---------|--------------|----------------------|
| <b>M8</b>  | 0,5 - 3,0 | 17,5    | 10868080300  | 250                  |
|            | 3,0 - 6,0 | 20,5    | 10868080600  | 250                  |
| SW 11,0    | k 1,5     | dk 16,0 | li max. 13,0 | ↺ 25 Nm<br>↕ 23500 N |
| <b>M10</b> | 1,0 - 4,5 | 22,0    | 10868100450  | 250                  |
|            | 4,0 - 6,0 | 23,5    | 10868100600  | 250                  |
| SW 13,0    | k 2,0     | dk 19,0 | li max. 16,5 | ↺ 55 Nm<br>↕ 37000 N |
| <b>M12</b> | 1,5 - 5,0 | 25,0    | 10868120500  | 100                  |
|            |           |         |              |                      |
| SW 16,0    | k 2,0     | dk 23,0 | li max. 19,0 | ↺ 85 Nm<br>↕ 56000 N |