





Écrous à sertir en aveugle HEXATOP-E-KLSK

inox A2

tête affleurante | semi-hexagonal | ouvert



[1.4567]

M		I	N°	
M4	0,5 - 2,5	11,0	10879040250	500
SW 6,0	SW² 6,8	k 0,5	I ₁ max. 8,5	↻ 5 Nm ⬆ 6000 N
M5	0,5 - 3,0	12,0	10879050300	500
	3,0 - 4,5	13,5	10879050450	500
SW 7,0	SW² 8,0	k 0,5	I ₁ max. 9,0	↻ 7 Nm ⬆ 9500 N
M6	0,5 - 3,0	14,0	10879060300	500
	3,0 - 5,0	16,0	10879060500	500
SW 9,0	SW² 10,0	k 0,5	I ₁ max. 10,0	↻ 13 Nm ⬆ 16000 N

M		I	N°	
M8	0,5 - 3,0	16,0	10879080300	250
	3,0 - 5,5	18,5	10879080550	250
SW 11,0	SW² 12,0	k 0,5	I ₁ max. 11,5	↻ 25 Nm ⬆ 26000 N
M10	1,0 - 3,5	19,0	10879100350	250
SW 13,0	SW² 14,4	k 0,7	I ₁ max. 14,0	↻ 55 Nm ⬆ 39000 N
M12	1,0 - 4,0	24,0	10879120400	100
SW 16,0	SW² 17,3	k 0,7	I ₁ max. 19,0	↻ 85 Nm ⬆ 55000 N