




Écrous à sertir en aveugle SSM-R-KLSK

 **acier zingué**

tête affleurante | cylindrique cranté | ouvert



C4C [1.0303]

M		I	N°	
M3	0,3 - 1,5	9,0	10843030150	500
D 5,0	k 0,5	dk 6,0	l ₁ max. 6,2	↕ 3500 N
M4	0,3 - 2,0	10,0	10843040200	500
	2,0 - 4,0	13,0	10843040400	500
D 6,0	k 0,6	dk 7,0	l ₁ max. 7,0	↕ 5000 N
M5	0,3 - 2,5	12,0	10843050250	500
	2,5 - 4,0	14,0	10843050400	500
D 7,0	k 0,7	dk 8,0	l ₁ max. 7,0	↕ 8000 N
M6	0,3 - 2,5	15,0	10843060250	500
	2,5 - 5,0	17,0	10843060500	500
D 9,0	k 0,7	dk 10,0	l ₁ max. 8,5	↕ 12000 N

M		I	N°	
M8	0,5 - 3,5	17,0	10843080350	500
	3,5 - 5,0	20,0	10843080500	500
D 11,0	k 0,8	dk 12,0	l ₁ max. 10,0	↕ 18000 N
M10	0,5 - 4,5	21,0	10843100450	250
	4,5 - 6,0	22,0	10843100600	250
D 13,0	k 0,8	dk 14,0	l ₁ max. 12,5	↕ 25000 N
M12	1,0 - 4,0	23,0	10843120400	100
D 16,0	k 1,3	dk 17,0	l ₁ max. 16,0	↕ 32000 N