

Écrous à sertir en aveugle SSM-R




acier zingué

tête fraisée | cylindrique cranté | ouvert



DONNÉES
CAO
EN LIGNE

Série
845



C4C [1.0303]

M		I	N°	
M4	1,5 - 3,5	11,5	10845040350	500
	3,0 - 5,0	13,0	10845040500	500
D 6,0	k 1,5	d_k 8,3	l₁ max. 8,0	↕ 5000 N
M5	1,5 - 4,0	13,5	10845050400	500
	4,0 - 6,5	16,0	10845050650	500
D 7,0	k 1,5	d_k 9,3	l₁ max. 9,0	↕ 9000 N
M6	1,5 - 4,5	16,0	10845060450	500
	4,5 - 6,5	18,0	10845060650	500
D 9,0	k 1,5	d_k 11,3	l₁ max. 11,0	↕ 15000 N

M		I	N°	
M8	1,5 - 4,5	19,0	10845080450	500
	3,5 - 6,5	21,0	10845080650	500
D 11,0	k 1,5	d_k 13,3	l₁ max. 13,5	↕ 20000 N
M10	1,5 - 4,5	22,0	10845100450	250
	3,5 - 6,5	25,0	10845100650	250
D 13,0	k 1,6	d_k 15,7	l₁ max. 14,5	↕ 28000 N
M12	2,0 - 4,5	24,5	10845120450	100
	4,5 - 7,5	27,5	10845120750	100
D 16,0	k 1,9	d_k 19,0	l₁ max. 17,5	↕ 45000 N