

Écrous à sertir en aveugle SSM




acier zingué

tête fraisée | cylindrique lisse | ouvert



DONNÉES
CAO
EN LIGNE

Série
853



C4C [1.0303]

M		I	N°	
M4	1,5 - 3,5	11,5	10853040350	500
D 6,0	k 1,5	dk 8,3	l ₁ max. 8,0	↻ 4 Nm ↕ 5200 N
M5	1,5 - 4,0	13,0	10853050400	500
D 7,0	k 1,5	dk 9,3	l ₁ max. 9,0	↻ 6 Nm ↕ 9500 N
M6	1,5 - 4,5	16,0	10853060450	500
	4,5 - 6,0	17,5	10853060600	500
D 9,0	k 1,5	dk 11,3	l ₁ max. 11,0	↻ 11 Nm ↕ 16500 N

M		I	N°	
M8	1,5 - 4,5	18,5	10853080450	250
	4,5 - 6,0	20,0	10853080600	250
D 11,0	k 1,5	dk 13,3	l ₁ max. 13,5	↻ 24 Nm ↕ 23500 N
M10	3,0 - 4,5	22,0	10853100450	250
	4,5 - 6,0	23,5	10853100600	250
	6,0 - 9,0	26,5	10853100900	250
D 13,0	k 1,5	dk 15,2	l ₁ max. 16,5	↻ 50 Nm ↕ 37000 N