



M	min. 	L + 0,05 - 0,13	B	Min. longueur de filetage F	H	+ 0,08 	Distance minimale centre du trou / bord de la tôle	N°
M3	1,02	6,00	4,20	3,20	4,80	4,22	6,00	10492030006
		8,00		4,00				10492030008
		10,00						10492030010
		12,00		5,00				10492030012
		14,00						10492030014
		16,00		6,50				10492030016
		18,00						10492030018
		20,00		9,50				10492030020
		22,00						10492030022
		25,00						10492030025
3,5M3	1,02	6,00	5,39	3,20	6,40	5,41	7,10	10492035006
		8,00		4,00				10492035008
		10,00						10492035010
		12,00		5,00				10492035012
		14,00		6,50				10492035014
		16,00						10492035016
		18,00						10492035018
		20,00		9,50				10492035020
		22,00						10492035022
		25,00						10492035025

M	min. 	L + 0,05 - 0,13	B	Min. longueur de filetage F	H	+ 0,08 	Distance minimale centre du trou / bord de la tôle	N°
M4	1,27	6,00	7,12	3,20	7,90	7,14	8,40	10492040006
		8,00		4,00				10492040008
		10,00						10492040010
		12,00		5,00				10492040012
		14,00		6,50				10492040014
		16,00						10492040016
		18,00						10492040018
		20,00		9,50				10492040020
		22,00						10492040022
		25,00						10492040025
M5	1,27	6,00	7,12	3,20	7,90	7,14	8,40	10492050006
		8,00		4,00				10492050008
		10,00						10492050010
		12,00		5,00				10492050012
		14,00		6,50				10492050014
		16,00						10492050016
		18,00						10492050018
		20,00		9,50				10492050020
		22,00						10492050022
		25,00						10492050025

Colonnettes à sertir à la presse en acier inoxydable (série AISI 400), adaptées pour la pose dans les tôles d'une dureté **supérieure à HRB 80 (jusqu'à 88)**.



Les colonnettes avec filetage, 3,5M3, offrent une épaisseur de paroi plus importante pour la taille de filetage M3.