



Colonnettes à sertir à la presse en acier inoxydable (série AISI 300), adaptées pour la pose dans les tôles d'une dureté **jusqu'à** HRB 70.

M		min. L + 0,05 - 0,13	D ± 0,25	d1 ± 0,13	B - 0,13	H	 Distance minimale centre du trou / bord de la tôle + 0,08	N°
M2,5		4,00	1,02	3,20	4,20	4,80	4,20	10486025004
		6,00						10486025006
		8,00						10486025008
		10,00						10486025010
		12,00						10486025012
M3		3,00	1,02	3,20	4,20	4,80	4,22	10486030003
		4,00						10486030004
		5,00						10486030005
		6,00						10486030006
		7,00						10486030007
		8,00						10486030008
		10,00						10486030010
		12,00						10486030012
		14,00						10486030014
		16,00						10486030016
3,5M3		3,00	1,02	3,20	5,39	6,40	5,41	10486035003
		4,00						10486035004
		5,00						10486035005
		6,00						10486035006
		7,00						10486035007
		8,00						10486035008
		10,00						10486035010
		12,00						10486035012
		14,00						10486035014
		16,00						10486035016
		18,00						10486035018

M		min. L + 0,05 - 0,13	D ± 0,25	d1 ± 0,13	B - 0,13	H	 Distance minimale centre du trou / bord de la tôle + 0,08	N°
M4		3,00	1,27	4,80	7,12	7,90	7,14	10486040003
		4,00						10486040004
		6,00						10486040006
		8,00						10486040008
		10,00						10486040010
		12,00						10486040012
		14,00						10486040014
		16,00						10486040016
		18,00						10486040018
		20,00						10486040020
M5		4,00	1,27	5,35	7,12	7,90	7,14	10486050004
		6,00						10486050006
		8,00						10486050008
		10,00						10486050010
		12,00						10486050012
		14,00						10486050014
		16,00						10486050016
		18,00						10486050018
		20,00						10486050020
		22,00						10486050022
		25,00						10486050025



Les colonnettes avec filetage, 3,5M3, offrent une épaisseur de paroi plus importante pour la taille de filetage M3.