



Écrous à sertir à la presse en acier inoxydable (série AISI 300), adaptés pour la pose dans les tôles d'une dureté **jusqu'à HRB 70**.

M		E ± 0,25	T ± 0,25	A max.	C max.	 + 0,08	Distance minimale centre du trou / bord de la tôle	N°
M2	0,80	6,30	1,50	0,77	4,20	4,22	4,80	10431020000
	1,00			0,97				10431020001
	1,40			1,38				10431020002
M2,5	0,80	6,30	1,50	0,77	4,20	4,22	4,80	10431025000
	1,00			0,97				10431025001
	1,40			1,38				10431025002
M3	0,80	6,30	1,50	0,77	4,20	4,22	4,80	10431030000
	1,00			0,97				10431030001
	1,40			1,38				10431030002

V-CLSS

M		E ± 0,25	T ± 0,25	A max.	C max.	 + 0,08	Distance minimale centre du trou / bord de la tôle	N°
M4	0,80	7,90	2,00	0,77	5,38	5,41	6,90	10431040000
	1,00			0,97				10431040001
	1,40			1,38				10431040002
M5	0,80	8,70	2,00	0,77	6,38	6,40	7,10	10431050000
	1,00			0,97				10431050001
	1,40			1,38				10431050002
M6	1,20	11,05	4,08	1,15	8,72	8,75	8,60	10431060000
	1,40			1,38				10431060001
	2,30			2,21				10431060002
M8	1,40	12,65	5,47	1,38	10,47	10,50	9,70	10431080001
	2,30			2,21				10431080002