



Colonnettes à sertir à la presse en acier trempé, adaptées pour la pose dans les tôles d'une dureté **jusqu'à HRB 80**.

M		L + 0,05 - 0,13	D ± 0,25	d1 ± 0,13	B - 0,13	H	 + 0,08	Distance minimale centre du trou / bord de la tôle	N°
M2	1,02	4,00	0,00	2,50	4,20	4,80	4,20	6,00	10485020004
		6,00							10485020006
		8,00							10485020008
		10,00	4,00						10485020010
		12,00							10485020012
M2,5	1,02	4,00	0,00	3,20	4,20	4,80	4,20	6,00	10485025004
		6,00							10485025006
		8,00							10485025008
		10,00	4,00						10485025010
		12,00							10485025012
M3	1,02	3,00	0,00	3,20	4,20	4,80	4,22	6,00	10485030003
		4,00							10485030004
		5,00							10485030005
		6,00							10485030006
		7,00							10485030007
		8,00							10485030008
		10,00							10485030010
		12,00	4,00						10485030012
		14,00							10485030014
		16,00	8,00						10485030016
		18,00							10485030018
3,5M3	1,02	3,00	0,00	3,20	5,39	6,40	5,41	6,80	10485035003
		4,00							10485035004
		5,00							10485035005
		6,00							10485035006
		7,00							10485035007
		8,00							10485035008
		10,00							4,00
		12,00	10485035012						
		14,00	8,00						10485035014
		16,00							10485035016
		18,00							10485035018

M		L + 0,05 - 0,13	D ± 0,25	d1 ± 0,13	B - 0,13	H			N°
M4	1,27	3,00	0,00	4,80	7,12	7,90	7,14	8,00	10485040003
		4,00							10485040004
		6,00							10485040006
		8,00							10485040008
		10,00	4,00						10485040010
		12,00							10485040012
		14,00							10485040014
		16,00	8,00						10485040016
		18,00							10485040018
		20,00							10485040020
		22,00	11,00						10485040022
		25,00							10485040025
		M5	1,27						4,00
6,00	10485050006								
8,00	10485050008								
10,00	10485050010								
12,00	4,00			10485050012					
14,00				10485050014					
16,00				10485050016					
18,00	8,00			10485050018					
20,00				10485050020					
22,00				10485050022					
25,00	11,00			10485050025					



Les colonnettes avec filetage 3,5M3 offrent une épaisseur de paroi plus importante pour la taille de filetage M3.