



Colonnets à sertir à la presse en acier inoxydable (série AISI 400), adaptées pour la pose dans les tôles d'une dureté **supérieure à HRB 80 (jusqu'à 88)**.

M	 min. + 0,05 - 0,13	L ± 0,25	D ± 0,13	d1 - 0,13	B	H	 + 0,08	Distance minimale centre du trou / bord de la tôle	N°					
M3	1,02	3,00	0,00	3,20	4,20	4,80	4,22	6,00	10487030003					
		4,00							10487030004					
		6,00							10487030006					
		8,00							10487030008					
		10,00	4,00						3,20	4,20	4,80	4,22	6,00	10487030010
		12,00												10487030012
		14,00												10487030014
		16,00	8,00											10487030016
18,00	10487030018													
3,5M3	1,02	3,00	0,00	3,20	5,39	6,40	5,41	7,10						10487035003
		4,00												10487035004
		6,00												10487035006
		8,00							10487035008					
		10,00	4,00						3,20	5,39	6,40	5,41	7,10	10487035010
		12,00												10487035012
		14,00												10487035014
		16,00	8,00											10487035016
		18,00												10487035018

M		min. L + 0,05 - 0,13	D ± 0,25	d1 ± 0,13	B - 0,13	H  + 0,08	Distance minimale centre du trou / bord de la tôle	N°	
M4	1,27	4,00	0,00	4,80	7,12	7,90	7,14	8,40	10487040004
		6,00							10487040006
		8,00							10487040008
		10,00							10487040010
		12,00	4,00						10487040012
		14,00							10487040014
		16,00							10487040016
		18,00							10487040018
		20,00	8,00						10487040020
		22,00							10487040022
		25,00							10487040025
M5	1,27	4,00	0,00	5,35	7,12	7,90	7,14	8,40	10487050004
		6,00							10487050006
		8,00							10487050008
		10,00							10487050010
		12,00	4,00						10487050012
		14,00							10487050014
		16,00							10487050016
		18,00							10487050018
		20,00	8,00						10487050020
		22,00							10487050022
		25,00							10487050025

 Les colonnettes avec filetage 3,5M3 offrent une épaisseur de paroi plus importante pour la taille de filetage M3.