



Écrous à sertir à la presse V-S / V-SS

 acier zingué

DONNÉES
CAO
EN LIGNE

Série
430



Écrous à sertir à la presse en acier trempé, adaptés pour la pose dans les tôles d'une dureté **jusqu'à HRB 80**.

M	min. 	E ± 0,25	T ± 0,25	A max.	C max.	 + 0,08	Distance minimale centre du trou / bord de la tôle	N°
M2	0,80			0,77				10430020000
	1,00	6,30	1,50	0,97	4,22	4,22	4,80	10430020001
	1,40			1,38				10430020002
M2,5	0,80			0,77				10430025000
	1,00	6,30	1,50	0,97	4,22	4,22	4,80	10430025001
	1,40			1,38				10430025002
M3	0,80			0,77				10430030000
	1,00	6,30	1,50	0,97	4,22	4,22	4,80	10430030001
	1,40			1,38				10430030002
M4	0,80			0,77				10430040000
	1,00	7,90	2,00	0,97	5,38	5,41	6,90	10430040001
	1,40			1,38				10430040002

M	min. 	E ± 0,25	T ± 0,25	A max.	C max.	 + 0,08	Distance minimale centre du trou / bord de la tôle	N°
V-SS M5	0,80			0,77				10430050000
	1,00	8,70	2,00	0,97	6,38	6,40	7,10	10430050001
	1,40			1,38				10430050002
M6	1,20			1,15				10430060000
	1,40	11,05	4,08	1,38	8,72	8,75	8,60	10430060001
	2,30			2,21				10430060002
M8	1,40	12,65	5,47	1,38	10,47	10,50	9,70	10430080001
	2,30			2,21				10430080002
M10	2,31	17,35	7,48	2,21	13,97	14,00	13,50	10430100001
	3,18			3,05				10430100002
M12	3,18	20,55	8,50	3,05	16,95	17,00	16,00	10430120001