



Écrous à sertir à la presse V-SP

 **Inox série 400**

pour tôles dures

DONNÉES
CAO
EN LIGNE

Série
435



Écrous à sertir à la presse en acier inoxydable (série AISI 400), adaptés pour la pose dans les tôles d'une dureté **supérieure à HRB 80 (jusqu'à 90)**.

M	min. 	E ± 0,25	T ± 0,25	A max.	C max.	 + 0,08	Distance minimale centre du trou / bord de la tôle	N°
M2,5	0,80			0,77				10435025000
	1,00	6,30	1,50	0,97	4,20	4,22	4,80	10435025001
	1,40			1,38				10435025002
M3	0,80			0,77				10435030000
	1,00	6,30	1,50	0,97	4,20	4,22	4,80	10435030001
	1,40			1,38				10435030002

M	min. 	E ± 0,25	T ± 0,25	A max.	C max.	 + 0,08	Distance minimale centre du trou / bord de la tôle	N°
M4	0,80			0,77				10435040000
	1,00	7,90	2,00	0,97	5,38	5,41	6,90	10435040001
	1,40			1,38				10435040002
M5	0,80			0,77				10435050000
	1,00	8,70	2,00	0,97	6,33	6,40	7,10	10435050001
	1,40			1,38				10435050002
M6	1,40	11,05	4,08	1,38	8,73	8,75	8,60	10435060001