## Goujons à sertir à la presse V-CFHC


Inox série 300


ût long | pour le montage dans trou borgne











Goujons à sertir à la presse en acier inoxydable (série AISI 300), adaptés pour la pose dans les tôles d'une dureté jusqu'à HRB 70.

M	min.	<b>L</b> ± 0,40	<b>E</b> ± 0,25	C max.	Α	S max.	+ 0,08	Mindestabstand Lochmitte/ Blechrand	Bohrtiefe	N <sub>0</sub>
M3	2,40	6,00	5,21	4,35	1,80	2,40	4,37	4,00	1.91	10481030006
		8,00								10481030008
		10,00								10481030010
		12,00								10481030012
		16,00								10481030016
		20,00								10481030020
M4	2,40	6,00	8,33	7,35	1,80	2,40	7,37	5,60	1.91	10481040006
		8,00								10481040008
		10,00								10481040010
		12,00								10481040012
		16,00								10481040016
		20,00								10481040020
		25,00								10481040025
M5	2,40	10,00	8,89	7,90	1,80	2,40	7,93	6,40	1.91	10481050010
		12,00								10481050012
		16,00								10481050016
		20,00								10481050020
		25,00								10481050025

Trou max. pièce montée égal au trou dans la tôle + 0,6 mm.