



EN AW-5019 [AlMg5]

d	l*1		Nr.	
3,2	6,5	0,5 - 2,0	10900032065	500
	8,0	2,0 - 3,5	10900032080	500
	9,5	3,5 - 5,0	10900032095	500
	11,0	5,0 - 6,5	10900032110	500
	12,5	6,5 - 8,0	10900032125	500
dk 6,1 -0,3	dm 1,7	k 1,1 ±0,15	3,3 mm 1100 N 1450 N	
4,0	8,0	1,5 - 3,5	10900040080	500
	9,5	3,5 - 5,0	10900040095	500
	11,0	5,0 - 6,5	10900040110	500
	12,5	6,5 - 8,0	10900040125	500
	14,5	8,0 - 10,0	10900040145	500
dk 8,0 -0,4	dm 2,2	k 1,3 ±0,2	4,1 mm 1600 N 2200 N	

d	l*1		Nr.	
4,8	8,0	0,5 - 3,5	10900048080	500
	9,5	3,5 - 5,0	10900048095	500
	11,0	5,0 - 6,5	10900048110	500
	13,0	6,5 - 8,0	10900048130	500
	14,5	7,5 - 9,5	10900048145	500
	16,0	9,5 - 11,0	10900048160	500
	18,0	11,0 - 13,0	10900048180	500
	21,0	12,0 - 16,0	10900048210	500
dk 9,6 -0,4	dm 2,7	k 1,5 ±0,2	4,9 mm 2200 N 3100 N	
6,4	12,5	1,5 - 6,5	10900064125	500
	15,5	4,5 - 9,5	10900064155	500
dk 12,7 -0,4	dm 3,7	k 2,0 ±0,3	6,5 mm 3600 N 4900 N	