



EN AW-5019 [AlMg5]

d	l +1		N°		
3,2	6,5	0,5 - 2,0	10902032065	500	
	8,0	2,0 - 3,5	10902032080	500	
	9,5	3,5 - 5,0	10902032095	500	
	11,0	5,0 - 6,5	10902032110	500	
	12,5	6,5 - 8,0	10902032125	500	
d _k 6,1 -0,3	d _m 1,7	k 1,1 ±0,15	 3,3 mm	 1100 N	 1450 N
4,0	8,0	1,5 - 3,5	10902040080	500	
	9,5	3,5 - 5,0	10902040095	500	
	11,0	5,0 - 6,5	10902040110	500	
	12,5	6,5 - 8,0	10902040125	500	
d _k 8,0 -0,4	d _m 2,2	k 1,3 ±0,2	 4,1 mm	 1600 N	 2200 N

d	l +1		Nº		
4,8	8,0	2,0 - 3,5	10902048080	500	
	9,5	3,5 - 5,0	10902048095	500	
	11,0	5,0 - 6,5	10902048110	500	
	12,5	6,0 - 7,5	10902048125	500	
	14,0	7,5 - 9,0	10902048140	500	
	16,0	9,5 - 11,0	10902048160	500	
	18,0	11,0 - 13,0	10902048180	500	
	21,0	12,0 - 16,0	10902048210	500	
	25,0	14,0 - 19,0	10902048250	500	
d _k 9,6 -0,4	d _m 2,7	k 1,5 ±0,2	 4,9 mm	 2200 N	 3100 N