



EN AW-5019 [AlMg5]

d	l +1		No.	
3,2	6,5	0,5 - 2,0	10902032065	500
	8,0	1,5 - 3,5	10902032080	500
	9,5	3,0 - 5,0	10902032095	500
	11,0	4,5 - 6,5	10902032110	500
	12,5	6,0 - 8,0	10902032125	500
dk 6,0 -0,3	dm 1,7	k 1,1 ±0,15	 3,3 mm  1100 N  1450 N	
4,0	8,0	0,5 - 3,5	10902040080	500
	9,5	3,0 - 5,0	10902040095	500
	11,0	4,5 - 6,5	10902040110	500
	12,5	6,0 - 8,0	10902040125	500
dk 8,0 -0,4	dm 2,2	k 1,3 ±0,2	 4,1 mm  1700 N  2700 N	

CERT

d	l +1		No.	
4,8	8,0	0,5 - 3,5	10902048080	500
	9,5	3,0 - 5,0	10902048095	500
	11,0	4,5 - 6,5	10902048110	500
	12,5	6,0 - 8,0	10902048125	500
	14,0	7,5 - 9,5	10902048140	500
	16,0	9,0 - 11,0	10902048160	500
	18,0	10,5 - 13,0	10902048180	500
	21,0	12,5 - 16,0	10902048210	500
	25,0	16,0 - 20,0	10902048250	500
dk 9,5 -0,4	dm 2,7	k 1,5 ±0,2	 4,9 mm  2480 N  3540 N	