



Nut V-SP

 **Stainless steel 400 series**

CAD
DATA
ONLINE

Series
435



Self-clinching nuts of stainless steel (AISI 400 series), suitable for use in metal sheets with hardnesses **above HRB 80 (up to HRB 90)**.

M	min. 	E ± 0,25	T ± 0,25	A max.	C max.	 + 0,08	Distance minimale centre du trou / bord de la tôle	No.
M2,5	0,80			0,77				10435025000
	1,00	6,30	1,50	0,97	4,20	4,22	4,80	10435025001
	1,40			1,38				10435025002
M3	0,80			0,77				10435030000
	1,00	6,30	1,50	0,97	4,20	4,22	4,80	10435030001
	1,40			1,38				10435030002

M	min. 	E ± 0,25	T ± 0,25	A max.	C max.	 + 0,08	Distance minimale centre du trou / bord de la tôle	No.
M4	0,80			0,77				10435040000
	1,00	7,90	2,00	0,97	5,38	5,41	6,90	10435040001
	1,40			1,38				10435040002
M5	0,80			0,77				10435050000
	1,00	8,70	2,00	0,97	6,33	6,40	7,10	10435050001
	1,40			1,38				10435050002
M6	1,40	11,05	4,08	1,38	8,73	8,75	8,60	10435060001