



Self-clinching stand-offs of stainless steel (AISI 300 series), suitable for use in sheet metal with hardnesses **up to HRB 70**.

M		L + 0,05 - 0,13	B	Mindestvollge- windelänge F	H	 + 0,08	Distance minimale centre du trou / bord de la tôle	No.
M3	1,02	6,00	4,19	3,20	4,80	4,22	6,00	10491030006
		8,00		4,00				10491030008
		10,00						10491030010
		12,00						10491030012
		14,00		6,50				10491030014
		16,00						10491030016
		18,00						10491030018
		20,00		9,50				10491030020
		22,00						10491030022
		25,00						10491030025
3,5M3	1,02	6,00	5,38	3,20	6,40	5,41	6,80	10491035006
		8,00		4,00				10491035008
		10,00						10491035010
		12,00						10491035012
		14,00		6,50				10491035014
		16,00						10491035016
		18,00						10491035018
		20,00		9,50				10491035020
		22,00						10491035022
		25,00						10491035025

M		L + 0,05 - 0,13	B	Mindestvollge- windelänge F	H	 + 0,08	Distance minimale centre du trou / bord de la tôle	No.
M4	1,27	8,00	7,10	4,00	7,90	7,14	8,00	10491040008
		10,00						10491040010
		12,00		5,00				10491040012
		14,00		6,50				10491040014
		16,00						10491040016
		18,00		9,50				10491040018
		20,00						10491040020
		22,00						10491040022
		25,00						10491040025
M5	1,27	8,00	7,10	4,00	7,90	7,14	8,00	10491050008
		10,00						10491050010
		12,00		5,00				10491050012
		14,00		6,50				10491050014
		16,00						10491050016
		18,00		9,50				10491050018
		20,00						10491050020
		22,00						10491050022
		25,00						10491050025



Stand-offs with 3.5 M3 threads offer a greater wall thickness for thread size M3.