



Self-clinching stand-offs of stainless steel (AISI 400 series), suitable for use in metal sheets with hardnesses **above HRB 80 (up to HRB 88)**.

M	 min.	L + 0,05 - 0,13	D ± 0,25	d1 ± 0,13	B - 0,13	H 	 + 0,08	Distance minimale centre du trou / bord de la tôle	No.
M3	1,02	3,00	0,00	3,20	4,20	4,80	4,22	6,00	10487030003
		4,00							10487030004
		6,00							10487030006
		8,00							10487030008
		10,00	4,00						10487030010
		12,00							10487030012
		14,00							10487030014
		16,00	8,00						10487030016
		18,00							10487030018
3,5M3	1,02	3,00	0,00	3,20	5,39	6,40	5,41	7,10	10487035003
		4,00							10487035004
		6,00							10487035006
		8,00							10487035008
		10,00	4,00						10487035010
		12,00							10487035012
		14,00							10487035014
		16,00	8,00						10487035016
		18,00							10487035018

M	 min.	L + 0,05 - 0,13	D ± 0,25	d1 ± 0,13	B - 0,13	H 	 + 0,08	Distance minimale centre du trou / bord de la tôle	No.
M4	1,27	4,00	0,00	4,80	7,12	7,90	7,14	8,40	10487040004
		6,00							10487040006
		8,00							10487040008
		10,00	4,00						10487040010
		12,00							10487040012
		14,00							10487040014
		16,00	8,00						10487040016
		18,00							10487040018
		20,00							10487040020
		22,00	11,00						10487040022
25,00	10487040025								
M5	1,27	4,00	0,00	5,35	7,12	7,90	7,14	8,40	10487050004
		6,00							10487050006
		8,00							10487050008
		10,00	4,00						10487050010
		12,00							10487050012
		14,00							10487050014
		16,00	8,00						10487050016
		18,00							10487050018
		20,00							10487050020
		22,00	11,00						10487050022
		25,00							10487050025

 Stand-offs with 3.5 M3 threads offer a greater wall thickness for thread size M3.