



# Einpressgewindebolzen V-FHL für geringe Randabstände



 Stahl verzinkt



CAD  
DATEN  
ONLINE


Serie  
**465**



Einpressgewindebolzen aus gehärtetem Stahl, geeignet für die Verarbeitung in Blechen mit Härten **bis HRB 80**.

| M           | min.<br> | L<br>± 0,40 | E<br>± 0,40 | <br>+ 0,08 | S<br>max. | Mindest-<br>abstand<br>Lochmittel/<br>Blechrand | Nr.         |
|-------------|---|-------------|-------------|---|-----------|---|-------------|
| <b>M2,5</b> | 1,00  | 6,00        | 3,15        | 2,50  | 2,10      | 2,80  | 10465025006 |
|             |   | 8,00        |             |   |           |   | 10465025008 |
|             |   | 10,00       |             |   |           |   | 10465025010 |
|             |   | 12,00       |             |   |           |   | 10465025012 |
|             |   | 15,00       |             |   |           |   | 10465025015 |
|             |   | 18,00       |             |   |           |   | 10465025018 |
| <b>M3</b>   | 1,00  | 6,00        | 3,65        | 3,00  | 2,10      | 3,30  | 10465030006 |
|             |   | 8,00        |             |   |           |   | 10465030008 |
|             |   | 10,00       |             |   |           |   | 10465030010 |
|             |   | 12,00       |             |   |           |   | 10465030012 |
|             |   | 15,00       |             |   |           |   | 10465030015 |
|             |   | 18,00       |             |   |           |   | 10465030018 |
|             |   | 25,00       |             |   |           |   | 10465030025 |

| M         | min.<br> | L<br>± 0,40 | E<br>± 0,40 | <br>+ 0,08 | S<br>max. | Mindest-<br>abstand<br>Lochmittel/<br>Blechrand | Nr.         |
|-----------|---|-------------|-------------|---|-----------|---|-------------|
| <b>M4</b> | 1,00  | 6,00        | 4,65        | 4,00  | 2,40      | 4,30  | 10465040006 |
|           |   | 8,00        |             |   |           |   | 10465040008 |
|           |   | 10,00       |             |   |           |   | 10465040010 |
|           |   | 12,00       |             |   |           |   | 10465040012 |
|           |   | 15,00       |             |   |           |   | 10465040015 |
|           |   | 18,00       |             |   |           |   | 10465040018 |
|           |   | 20,00       |             |   |           |   | 10465040020 |
|           |   | 25,00       |             |   |           |   | 10465040025 |
|           |   | 35,00       |             |   |           |   | 10465040035 |
| <b>M5</b> | 1,00  | 8,00        | 5,90        | 5,00  | 2,70      | 5,60  | 10465050008 |
|           |   | 10,00       |             |   |           |   | 10465050010 |
|           |   | 12,00       |             |   |           |   | 10465050012 |
|           |   | 15,00       |             |   |           |   | 10465050015 |
|           |   | 18,00       |             |   |           |   | 10465050018 |
|           |   | 20,00       |             |   |           |   | 10465050020 |
|           |   | 25,00       |             |   |           |   | 10465050025 |
|           |   | 30,00       |             |   |           |   | 10465050030 |
|           |   | 35,00       |             |   |           |   | 10465050035 |

 Max. Loch montiertes Teil ist gleich Lochgröße  
im Blech + 0,6 mm.